




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F21K 2/06, A01K 85/01, 75/02	A1	(11) International Publication Number: WO 97/31217 (43) International Publication Date: 28 August 1997 (28.08.97)
(21) International Application Number: PCT/KR96/00210 (22) International Filing Date: 22 November 1996 (22.11.96) (30) Priority Data: 1996/2693 U 23 February 1996 (23.02.96) KR (71)(72) Applicant and Inventor: LEE, Keun, Ji [KR/KR]; 7-605, Imkwang Apartment, 1015, Pangbae-dong, Socho-gu, Seoul 137-060 (KR). (74) Agent: LEE, Dae, Sun; 6F Chongkundang Building, 441, Shipchong 2-dong, Pupyong-gu, Incheon 403-132 (KR).		(81) Designated States: CN (Utility model), DE (Utility model), JP (Utility model), US, European patent (IT). Published <i>With international search report.</i>

(54) Title: MULTI-LIGHT EMITTING CHEMI-LIGHT**(57) Abstract**

This invention relates to a multi-light emitting chemi-light. According to the invention, there is provided a chemi-light which includes a flexible and light-transmittable tube (6) which contains reactants (6) and ampule (12) in which other reactants (8) are contained, wherein said tube (10) is partitioned by at least one partition (14) to form at least two chambers (16, 18), and each of said chamber (16, 18) contains reactant (6a) and reactant (6b) respectively, and each of said chamber (16, 18) also contains each ampule (12a, 12b), and said ampules (12a, 12b) contain reactant (8a) reactable with said reactant (6a) and reactant (8b) reactable with said reactant (6b) respectively to emit the different color lights.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

MULTI-LIGHT EMITTING CHEMI-LIGHT

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to a multi-light emitting chemi-light, and in particular to a chemi-light which emits light in multiple colors so that it looks more distinctive to eyes of people.

(Background Art)

'Chemi-luminescence' or 'Chemical light-emitting' is a reaction in which a reactant transitting from an exited state to a ground state emits a light energy. This reaction could be regarded as a backward reaction of photochemical reaction. In chemi-luminescence, atoms or molecules which are electrically exited during the chemical reaction come to vibrate or collide to other adjacent ones, and these unstable atoms or molecules should emit the light. By selecting the reacting substances, or by adding different fluorescers or by mixing two or more fluorescers, the chemi-light would emit a predetermined-colored lights.

Recently, the chemi-luminescence are practically applied for fishing, decoration and other leisure goods in the name of 'chemi-light' or 'chemical light'. Fig. 1 shows the chemi-light(5) attached to float(4) of fishing rod(2). This light-emitting chemi-light(5) makes it easy for a fisherman to keep his eyes on the float(4) at night.

As shown in Fig. 2, the chemi-light(5) is composed of a flexible and light-transmittable tube(10) containing a predetermined liquid reactant A(6) and glass ampule(12). This ampule(12) also contains other liquid reactant B(8). The ampule(12) is dipped in reactant A(6). If the tube(10) is bent by fingers, the ampule(12) is to be broken. Then, the liquid reactant A(6) contained in the tube(10) and the liquid reactant B(8) contained in the ampule(12) are to be mixed to each other, and start to emit light. This chemi-light is now used for lighting of the outdoors leisure and military purposes as well as for night fishing goods.

But, the above mentioned chemi-light is formed by one tube and one ampule contained in said tube. Therefore, each of the tube and ampule should contain one kind of reactant or reactant mixture, so that

the chemi-light should have one combination of reactants. As a result, the chemi-light may issue one color light. That is, it should be impossible to change or diversify the color pattern of light in one chemi-light. Therefore, the chemi-light should look monotonous and less distinguishable.

SUMMARY OF THE INVENTION

The object of this invention is to solve the above mentioned problems by providing a new chemi-light which could emit multi-color light to change and diversify the light-emitting patterns and make it look colorful and more distinguishable to the eyes of person.

The above object is achieved by the invention of chemi-light which includes a flexible and light-transmittable tube(6) which contains reactants(6) and ampule(12) in which other reactants(8) are contained, wherein said tube(10) is partitioned by at least one partition(14) to form at least two chambers(16,18), and each of said chambers(16,18) contains reactant(6a) and reactant(6b) respectively, and each of said chambers(16,18) also contains each ampules(12a,12b), and said ampules(12a,12b) contain reactant(8a) reactable with said reactant(6a)

and reactant(8b) reactable with said reactant(6b) respectively to emit the different color lights.

Brief Description of the drawings.

The invention will be descibed in more detail with reference to the drawings in which ;

Fig. 1 is a view showing an exemplary use of the conventional chemi-light.

Fig. 2 is a partially broken view of the conventional chemi-light tube.

Fig. 3 is a partially broken view of the embodiment according to the invention.

Description of the preferred embodiment

Referring to Fig. 3, the chemi-light(5) comprises flexible and transparent or light-transmittable plastic tube(10) which is partitioned by a diaphragmic partition(14) to form two chambers(16,18). The shape of said tube(10) or the location of said partition(14) should be properly determined. Each chamber(16,18) contains liquid reactant(16a) and liquid reactant(16) repectively. Also, Each chamber(16,18) contains each glass

ampule(12a, 12b). Said ampules(12a,12b) are dipped in said reactants(6a,6b) respectively. And these ampules(12a,12b) contain other reactant(8a, 8b) respectively.

The combinations of said reactants are properly selected so that the color of light emitted by mixing of the reactant(6a) and reactant(8b) is visually distinctive and differentiated from the color of light emitted by mixing of the reactant(6b) and reactant(8b). For this purpose, the ingredients of reactant or added fluorescers should be differentiated.

If necessary, the tube(10) might be partitioned into three or more chambers, and each of the chambers might have each ampule. The combination of reactants in a chamber and the one in the corresponding ampule should be differentiated to achieve more colorful and more various light patterns.

According to the invention as described above, the tube(10) of chemi-light(5) has a case of plastic tube(10) which is partitioned into two or more chambers, and combinations of reactants properly selected to emit different colored lights should be contained in each chamber and the corresponding ampule. In order to lighten the chemi-light, all of

these ampule(12a,12b) in each chamber(16,18) should be broken by bending the tube(10). Then, by mixing of the different combination of reactants, each chamber(16,18) will emit the different color lights. As a result, the chemi-light could issue more colorful and more distinctive multi-colored light. The multi-colored pattern according to the invention might be applicable for the purpose of signal communication.

CLAIMS

1. Chemi-light which includes a flexible and light-transmittable tube(6) which contains reactants(6) and ampule(12) in which other reactants(8) are contained, wherein said tube(10) is partitioned by at least one partition(14) to form at least two chambers(16,18), and each of said chambers(16,18) contains reactant(6a) and reactant(6b) respectively, and each of said chambers(16,18) also contains each ampules(12a,12b), and said ampules(12a,12b) contain reactant(8a) reactable with said reactant(6a) and reactant(8b) reactable with said reactant(6b) respectively to emit the different color lights.

1/2

FIG. 1




FIG. 2





FIG. 3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 96/00210

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F 21 K 2/06; A 01 K 85/01, 75/02
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F 21 K 2/00; A 01 K 85/00, 75/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 638 584 A (LINDSAY) 27 January 1987 (27.01.87), fig.2A-2C; column 6, lines 64-67; column 7, lines 3-21.	1
X	US 5 390 086 A (HOLLAND) 14 February 1995 (14.02.95), fig.7; abstract; column 5, lines 29-58; column 6, lines 8-14.	1
X	US 5 383 100 A (KIKOS) 17 January 1995 (17.01.95), fig.8; abstract; column 3, lines 8-52.	1
P,X	US 5 508 893 A (NOWAK) 16 April 1996 (16.04.96), fig.4,5; abstract; column 3, lines 14-36; column 2, lines 23-29.	1
A	US 5 158 349 A (HOLLAND) 27 October 1992 (27.10.92), fig.3, abstract; column 4, lines 9-24.	1

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 March 1997 (28.03.97)

Date of mailing of the international search report

16 April 1997 (16.04.97)

Name and mailing address of the ISA/AT
AUSTRIAN PATENT OFFICE
Kohlmarkt 8-10
A-1014 Vienna
Facsimile No. 1/53424/535

Authorized officer

Kral

Telephone No.

1/53424/335

Form PCT/ISA/210 (second sheet) (July 1992)

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR 96/00210

In Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
US A 4638584	27-01-87	keine - none - rien	
US A 5390086	14-02-95	US A 5222797	29-06-93
US A 5383100	17-01-95	keine - none - rien	
US A 5508893	16-04-96	keine - none - rien	
US A 5158349	27-10-92	keine - none - rien	